

AS/NZS 13818.2:2002
ISO/IEC 13818-2:2000
ISO/IEC 13818-2:2000/Amdt 1:2001
ISO/IEC 13818-2:2000/Corr. 1:2002

Australian/New Zealand Standard™

**Information technology—Generic
coding of moving pictures and
associated audio information**

Part 2: Video

AS/NZS 13818.2:2002

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee IT-001, Information Systems—Interconnections. It was approved on behalf of the Council of Standards Australia on 23 August 2002 and on behalf of the Council of Standards New Zealand on 20 August 2002. It was published on 28 November 2002.

The following are represented on Committee IT-001:

Australian Bureau of Statistics
Australian Chamber of Commerce and Industry
Australian Communications Industry Forum
Australian Information Industry Association
Australian Telecommunications Users Group
Australian Vice-Chancellors Committee
Electrical Compliance Testing Association
Information Technology Association of New Zealand
Internet Industry Association
Telstra Corporation

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Australia web site at www.standards.com.au or Standards New Zealand web site at www.standards.co.nz and looking up the relevant Standard in the on-line catalogue.

Alternatively, both organizations publish an annual printed Catalogue with full details of all current Standards. For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia International or Standards New Zealand at the address shown on the back cover.

Australian/New Zealand Standard™

Information technology—Generic coding of moving pictures and associated audio information

Part 2: Video

Originated as part of AS/NZS 13818.2:1997, AS/NZS 13818.2 Supp 1:1999, AS/NZS 13818.2 Supp 2:1999, AS/NZS 13818.2 Supp 3:1999 and AS/NZS 13818.2 Supp 4:1999. AS/NZS 13818.2:1997, AS/NZS 13818.2 Supp 1:1999, AS/NZS 13818.2 Supp 2:1999, AS/NZS 13818.2 Supp 3:1999 and AS/NZS Supp 4:1999 jointly revised, amalgamated and redesignated as AS/NZS 13818.2:2002.

COPYRIGHT

© Standards Australia/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Jointly published by Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001 and Standards New Zealand, Private Bag 2439, Wellington 6020

ISBN 0 7337 4809 0

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee IT-001, Information Systems—Interconnections. This Standard is identical with and has been reproduced from ISO/IEC 13818-2:2000, *Information technology—Generic coding of moving pictures and associated audio information*, Part 2: Video, Amendment 1:2001 and Technical Corrigendum 1:2002 which are bound at the back of this Standard.

The objective of this Standard is to specify the coded representation of picture information for digital storage media and digital video communication and also to specify the decoding process.

This Standard is Part 2 of AS/NZS 13818, *Information technology—Generic coding of moving pictures and associated audio information*, which is published in parts as follows:

- Part 1: Systems
- Part 2: Video (this Standard)
- Part 3: Audio
- Part 4: Conformance testing
- Part 5: Software simulation
- Part 6: Extensions for DSM-CC
- Part 7: Advanced audio coding
- Part 9: Extension for real time interface for systems decoders
- Part 10: Conformance extensions for digital storage media command and control

The term ‘normative’ has been used in this Standard to define the application of the annex to which it applies. A ‘normative’ annex is an integral part of a Standard.

As this Standard is reproduced from an International Standard, the following applies:

- (a) Its number does not appear on each page of text and its identity is shown only on the cover and title page.
- (b) In the source text ‘this International Standard’ should read ‘this Australian/New Zealand Standard’.
- (c) A full point should be substituted for a comma when referring to a decimal marker.

References to International Standards should be replaced by references to equivalent Australian or Australian/New Zealand Standards, as follows:

<i>Reference to International Standard</i>		<i>Australian/New Zealand Standard</i>	
ISO/IEC			
11172	Information technology—Coding of moving pictures and associated audio for digital storage media at up to about 1.5 Mbit/s	4230	Information technology—Coding of moving pictures and associated audio for digital storage media at up to about 1.5 Mbit/s
11172-1	Part 1: Systems	4230.1	Part 1: Systems
11172-2	Part 2: Video	4230.2	Part 2: Video
11172-3	Part 3: Audio	4230.3	Part 3: Audio
10918	Information technology—Digital compression and coding of continuous-tone still images:	4473	Information technology—Digital compression and coding of continuous-tone still images
10918-1	Part 1: Requirements and guidelines	4473.1	Part 1: Requirements and guidelines

CONTENTS

	<i>Page</i>
Intro. 1 Purpose.....	v
Intro. 2 Application.....	v
Intro. 3 Profiles and levels	v
Intro. 4 The scalable and the non-scalable syntax	vi
1 Scope	1
2 Normative references	1
3 Definitions	2
4 Abbreviations and symbols.....	7
4.1 Arithmetic operators.....	7
4.2 Logical operators.....	8
4.3 Relational operators.....	8
4.4 Bitwise operators.....	8
4.5 Assignment.....	8
4.6 Mnemonics	8
4.7 Constants	9
5 Conventions	9
5.1 Method of describing bitstream syntax.....	9
5.2 Definition of functions	10
5.3 Reserved, forbidden and marker_bit.....	10
5.4 Arithmetic precision	11
6 Video bitstream syntax and semantics	11
6.1 Structure of coded video data	11
6.2 Video bitstream syntax	21
6.3 Video bitstream semantics.....	36
7 The video decoding process.....	61
7.1 Higher syntactic structures	61
7.2 Variable length decoding.....	62
7.3 Inverse scan	64
7.4 Inverse quantisation.....	66
7.5 Inverse DCT	69
7.6 Motion compensation	69
7.7 Spatial scalability.....	83
7.8 SNR scalability	92
7.9 Temporal scalability	99
7.10 Data partitioning	102
7.11 Hybrid scalability	103
7.12 Output of the decoding process	104
8 Profiles and levels.....	106
8.1 ISO/IEC 11172-2 compatibility.....	109
8.2 Relationship between defined profiles.....	109
8.3 Relationship between defined levels	111
8.4 Scalable layers.....	111
8.5 Parameter values for defined profiles, levels and layers.....	114
8.6 Compatibility requirements on decoders.....	115
9 Registration of Copyright Identifiers	117
9.1 General	117
9.2 Implementation of a Registration Authority (RA).....	118

	<i>Page</i>
Annex A – Inverse discrete transform	119
Annex B – Variable length code tables	121
B.1 Macroblock addressing	121
B.2 Macroblock type	122
B.3 Macroblock pattern	127
B.4 Motion vectors	128
B.5 DCT coefficients	129
Annex C – Video buffering verifier	138
Annex D – Features supported by the algorithm	143
D.1 Overview	143
D.2 Video formats	143
D.3 Picture quality	144
D.4 Data rate control	144
D.5 Low delay mode	144
D.6 Random access/channel hopping	145
D.7 Scalability	145
D.8 Compatibility	151
D.9 Differences between this Specification and ISO/IEC 11172-2	151
D.10 Complexity	154
D.11 Editing encoded bitstreams	154
D.12 Trick modes	154
D.13 Error resilience	155
D.14 Concatenated sequences	162
Annex E – Profile and level restrictions	163
E.1 Syntax element restrictions in profiles	163
E.2 Permissible layer combinations	175
Annex F – Bibliography	197
Annex G – Registration Procedure	198
G.1 Procedure for the request of a Registered Identifier (RID)	198
G.2 Responsibilities of the Registration Authority	198
G.3 Responsibilities of parties requesting an RID	198
G.4 Appeal procedure for denied applications	199
Annex H – Registration Application Form	200
H.1 Contact information of organization requesting a Registered Identifier (RID)	200
H.2 Statement of an intention to apply the assigned RID	200
H.3 Date of intended implementation of the RID	200
H.4 Authorized representative	200
H.5 For official use only of the Registration Authority	200
Annex J – 4:2:2 Profile test results	202
J.1 Introduction	202
Annex K – Patents	207

INTRODUCTION

Intro. 1 Purpose

This Part of this Recommendation | International Standard was developed in response to the growing need for a generic coding method of moving pictures and of associated sound for various applications such as digital storage media, television broadcasting and communication. The use of this Specification means that motion video can be manipulated as a form of computer data and can be stored on various storage media, transmitted and received over existing and future networks and distributed on existing and future broadcasting channels.

Intro. 2 Application

The applications of this Specification cover, but are not limited to, such areas as listed below:

BSS	Broadcasting Satellite Service (to the home)
CATV	Cable TV Distribution on optical networks, copper, etc.
CDAD	Cable Digital Audio Distribution
DSB	Digital Sound Broadcasting (terrestrial and satellite broadcasting)
DTTB	Digital Terrestrial Television Broadcasting
EC	Electronic Cinema
ENG	Electronic News Gathering (including SNG, Satellite News Gathering)
FSS	Fixed Satellite Service (e.g. to head ends)
HTT	Home Television Theatre
IPC	Interpersonal Communications (videoconferencing, videophone, etc.)
ISM	Interactive Storage Media (optical disks, etc.)
MMM	Multimedia Mailing
NCA	News and Current Affairs
NDB	Networked Database Services (via ATM, etc.)
RVS	Remote Video Surveillance
SSM	Serial Storage Media (digital VTR, etc.)

Intro. 3 Profiles and levels

This Specification is intended to be generic in the sense that it serves a wide range of applications, bitrates, resolutions, qualities and services. Applications should cover, among other things, digital storage media, television broadcasting and communications. In the course of creating this Specification, various requirements from typical applications have been considered, necessary algorithmic elements have been developed, and they have been integrated into a single syntax. Hence, this Specification will facilitate the bitstream interchange among different applications.

Considering the practicality of implementing the full syntax of this Specification, however, a limited number of subsets of the syntax are also stipulated by means of "profile" and "level". These and other related terms are formally defined in clause 3.

A "profile" is a defined subset of the entire bitstream syntax that is defined by this Specification. Within the bounds imposed by the syntax of a given profile it is still possible to require a very large variation in the performance of encoders and decoders depending upon the values taken by parameters in the bitstream. For instance, it is possible to specify frame sizes as large as (approximately) 2^{14} samples wide by 2^{14} lines high. It is currently neither practical nor economic to implement a decoder capable of dealing with all possible frame sizes.

In order to deal with this problem, "levels" are defined within each profile. A level is a defined set of constraints imposed on parameters in the bitstream. These constraints may be simple limits on numbers. Alternatively they may take the form of constraints on arithmetic combinations of the parameters (e.g. frame width multiplied by frame height multiplied by frame rate).

Bitstreams complying with this Specification use a common syntax. In order to achieve a subset of the complete syntax, flags and parameters are included in the bitstream that signal the presence or otherwise of syntactic elements that occur later in the bitstream. In order to specify constraints on the syntax (and hence define a profile), it is thus only necessary to constrain the values of these flags and parameters that specify the presence of later syntactic elements.

Intro. 4 The scalable and the non-scalable syntax

The full syntax can be divided into two major categories: One is the non-scalable syntax, which is structured as a super set of the syntax defined in ISO/IEC 11172-2. The main feature of the non-scalable syntax is the extra compression tools for interlaced video signals. The second is the scalable syntax, the key property of which is to enable the reconstruction of useful video from pieces of a total bitstream. This is achieved by structuring the total bitstream in two or more layers, starting from a standalone base layer and adding a number of enhancement layers. The base layer can use the non-scalable syntax, or in some situations conform to the ISO/IEC 11172-2 syntax.

Intro. 4.1 Overview of the non-scalable syntax

The coded representation defined in the non-scalable syntax achieves a high compression ratio while preserving good image quality. The algorithm is not lossless as the exact sample values are not preserved during coding. Obtaining good image quality at the bitrates of interest demands very high compression, which is not achievable with intra picture coding alone. The need for random access, however, is best satisfied with pure intra picture coding. The choice of the techniques is based on the need to balance a high image quality and compression ratio with the requirement to make random access to the coded bitstream.

A number of techniques are used to achieve high compression. The algorithm first uses block-based motion compensation to reduce the temporal redundancy. Motion compensation is used both for causal prediction of the current picture from a previous picture, and for non-causal, interpolative prediction from past and future pictures. Motion vectors are defined for each 16-sample by 16-line region of the picture. The prediction error, is further compressed using the Discrete Cosine Transform (DCT) to remove spatial correlation before it is quantised in an irreversible process that discards the less important information. Finally, the motion vectors are combined with the quantised DCT information, and encoded using variable length codes.

Intro. 4.1.1 Temporal processing

Because of the conflicting requirements of random access and highly efficient compression, three main picture types are defined. Intra Coded Pictures (I-Pictures) are coded without reference to other pictures. They provide access points to the coded sequence where decoding can begin, but are coded with only moderate compression. Predictive Coded Pictures (P-Pictures) are coded more efficiently using motion compensated prediction from a past intra or predictive coded picture and are generally used as a reference for further prediction. Bidirectionally-predictive Coded Pictures (B-Pictures) provide the highest degree of compression but require both past and future reference pictures for motion compensation. Bidirectionally-predictive coded pictures are never used as references for prediction (except in the case that the resulting picture is used as a reference in a spatially scalable enhancement layer). The organisation of the three picture types in a sequence is very flexible. The choice is left to the encoder and will depend on the requirements of the application. Figure Intro. 1 illustrates an example of the relationship among the three different picture types.




Figure Intro. 1 – Example of temporal picture structure

Intro. 4.1.2 Coding interlaced video

Each frame of interlaced video consists of two fields which are separated by one field-period. The Specification allows either the frame to be encoded as picture or the two fields to be encoded as two pictures. Frame encoding or field encoding can be adaptively selected on a frame-by-frame basis. Frame encoding is typically preferred when the video scene contains significant detail with limited motion. Field encoding, in which the second field can be predicted from the first, works better when there is fast movement.

Intro. 4.1.3 Motion representation – Macroblocks

As in ISO/IEC 11172-2, the choice of 16 by 16 macroblocks for the motion-compensation unit is a result of the trade-off between the coding gain provided by using motion information and the overhead needed to represent it. Each macroblock can be temporally predicted in one of a number of different ways. For example, in frame encoding, the prediction from the previous reference frame can itself be either frame-based or field-based. Depending on the type of the macroblock, motion vector information and other side information is encoded with the compressed prediction error in each macroblock. The motion vectors are encoded differentially with respect to the last encoded motion vectors using variable length codes. The maximum length of the motion vectors that may be represented can be programmed, on a picture-by-picture basis, so that the most demanding applications can be met without compromising the performance of the system in more normal situations.

It is the responsibility of the encoder to calculate appropriate motion vectors. This Specification does not specify how this should be done.

Intro. 4.1.4 Spatial redundancy reduction

Both source pictures and prediction errors have high spatial redundancy. This Specification uses a block-based DCT method with visually weighted quantisation and run-length coding. After motion compensated prediction or interpolation, the resulting prediction error is split into 8 by 8 blocks. These are transformed into the DCT domain where they are weighted before being quantised. After quantisation many of the DCT coefficients are zero in value and so two-dimensional run-length and variable length coding is used to encode the remaining DCT coefficients efficiently.

Intro. 4.1.5 Chrominance formats

In addition to the 4:2:0 format supported in ISO/IEC 11172-2 this Specification supports 4:2:2 and 4:4:4 chrominance formats.

Intro. 4.2 Scalable extensions

The scalability tools in this Specification are designed to support applications beyond that supported by single layer video. Among the noteworthy applications areas addressed are video telecommunications, video on Asynchronous Transfer Mode (ATM) networks, interworking of video standards, video service hierarchies with multiple spatial, temporal and quality resolutions, HDTV with embedded TV, systems allowing migration to higher temporal resolution HDTV, etc. Although a simple solution to scalable video is the simulcast technique which is based on transmission/storage of multiple independently coded reproductions of video, a more efficient alternative is scalable video coding, in which the bandwidth allocated to a given reproduction of video can be partially re-utilised in coding of the next reproduction of video. In scalable video coding, it is assumed that given a coded bitstream, decoders of various complexities can decode and display appropriate reproductions of coded video. A scalable video encoder is likely to have increased complexity when compared to a single layer encoder. However, this Recommendation | International Standard provides several different forms of scalabilities that address non-overlapping applications with corresponding complexities. The basic scalability tools offered are:

- data partitioning;
- SNR scalability;
- spatial scalability; and
- temporal scalability.

Moreover, combinations of these basic scalability tools are also supported and are referred to as *hybrid scalability*. In the case of basic scalability, two layers of video referred to as the *lower layer* and the *enhancement layer* are allowed, whereas in hybrid scalability up to three layers are supported. Tables Intro. 1 to Intro. 3 provide a few example applications of various scalabilities.

Table Intro. 1 – Applications of SNR scalability

Lower layer	Enhancement layer	Application
Recommendation ITU-R BT.601	Same resolution and format as lower layer	Two quality service for Standard TV (SDTV)
High Definition	Same resolution and format as lower layer	Two quality service for HDTV
4:2:0 high definition	4:2:2 chroma simulcast	Video production / distribution

Table Intro. 2 – Applications of spatial scalability

Base	Enhancement	Application
Progressive (30 Hz)	Progressive (30 Hz)	Compatibility or scalability CIF/SCIF
Interlace (30 Hz)	Interlace (30 Hz)	HDTV/SDTV scalability
Progressive (30 Hz)	Interlace (30 Hz)	ISO/IEC 11172-2/compatibility with this Specification
Interlace (30 Hz)	Progressive (60 Hz)	Migration to high resolution progressive HDTV

Table Intro. 3 – Applications of temporal scalability

Base	Enhancement	Higher	Application
Progressive (30 Hz)	Progressive (30 Hz)	Progressive (60 Hz)	Migration to high resolution progressive HDTV
Interlace (30 Hz)	Interlace (30 Hz)	Progressive (60 Hz)	Migration to high resolution progressive HDTV

Intro. 4.2.1 Spatial scalable extension

Spatial scalability is a tool intended for use in video applications involving telecommunications, interworking of video standards, video database browsing, interworking of HDTV and TV, etc., i.e. video systems with the primary common feature that a minimum of two layers of spatial resolution are necessary. Spatial scalability involves generating two spatial resolution video layers from a single video source such that the lower layer is coded by itself to provide the basic spatial resolution and the enhancement layer employs the spatially interpolated lower layer and carries the full spatial resolution of the input video source. The lower and the enhancement layers may either both use the coding tools in this Specification, or the ISO/IEC 11172-2 Standard for the lower layer and this Specification for the enhancement layer. The latter case achieves a further advantage by facilitating interworking between video coding standards. Moreover, spatial scalability offers flexibility in choice of video formats to be employed in each layer. An additional advantage of spatial scalability is its ability to provide resilience to transmission errors as the more important data of the lower layer can be sent over channel with better error performance, while the less critical enhancement layer data can be sent over a channel with poor error performance.

Intro. 4.2.2 SNR scalable extension

SNR scalability is a tool intended for use in video applications involving telecommunications, video services with multiple qualities, standard TV and HDTV, i.e. video systems with the primary common feature that a minimum of two layers of video quality are necessary. SNR scalability involves generating two video layers of same spatial resolution but different video qualities from a single video source such that the lower layer is coded by itself to provide the basic video quality and the enhancement layer is coded to enhance the lower layer. The enhancement layer when added back to the

lower layer regenerates a higher quality reproduction of the input video. The lower and the enhancement layers may either use this Specification or ISO/IEC 11172-2 Standard for the lower layer and this Specification for the enhancement layer. An additional advantage of SNR scalability is its ability to provide high degree of resilience to transmission errors as the more important data of the lower layer can be sent over channel with better error performance, while the less critical enhancement layer data can be sent over a channel with poor error performance.

Intro. 4.2.3 Temporal scalable extension

Temporal scalability is a tool intended for use in a range of diverse video applications from telecommunications to HDTV for which migration to higher temporal resolution systems from that of lower temporal resolution systems may be necessary. In many cases, the lower temporal resolution video systems may be either the existing systems or the less expensive early generation systems, with the motivation of introducing more sophisticated systems gradually. Temporal scalability involves partitioning of video frames into layers, whereas the lower layer is coded by itself to provide the basic temporal rate and the enhancement layer is coded with temporal prediction with respect to the lower layer, these layers when decoded and temporal multiplexed to yield full temporal resolution of the video source. The lower temporal resolution systems may only decode the lower layer to provide basic temporal resolution, whereas more sophisticated systems of the future may decode both layers and provide high temporal resolution video while maintaining interworking with earlier generation systems. An additional advantage of temporal scalability is its ability to provide resilience to transmission errors as the more important data of the lower layer can be sent over channel with better error performance, while the less critical enhancement layer can be sent over a channel with poor error performance.

Intro. 4.2.4 Data partitioning extension

Data partitioning is a tool intended for use when two channels are available for transmission and/or storage of a video bitstream, as may be the case in ATM networks, terrestrial broadcast, magnetic media, etc. The bitstream is partitioned between these channels such that more critical parts of the bitstream (such as headers, motion vectors, low frequency DCT coefficients) are transmitted in the channel with the better error performance, and less critical data (such as higher frequency DCT coefficients) is transmitted in the channel with poor error performance. Thus, degradation to channel errors are minimised since the critical parts of a bitstream are better protected. Data from neither channel may be decoded on a decoder that is not intended for decoding data partitioned bitstreams.

X

NOTES

AUSTRALIAN/NEW ZEALAND STANDARD

INFORMATION TECHNOLOGY – GENERIC CODING OF MOVING PICTURES AND ASSOCIATED AUDIO INFORMATION: VIDEO

1 Scope

This Recommendation | International Standard specifies the coded representation of picture information for digital storage media and digital video communication and specifies the decoding process. The representation supports constant bitrate transmission, variable bitrate transmission, random access, channel hopping, scalable decoding, bitstream editing, as well as special functions such as fast forward playback, fast reverse playback, slow motion, pause and still pictures. This Recommendation | International Standard is forward compatible with ISO/IEC 11172-2 and upward or downward compatible with EDTV, HDTV, SDTV formats.

This Recommendation | International Standard is primarily applicable to digital storage media, video broadcast and communication. The storage media may be directly connected to the decoder, or via communications means such as busses, LANs, or telecommunications links.

2 Normative references

The following Recommendations and International Standards contain provisions which, through reference in this text, constitute provisions of this Recommendation | International Standard. At the time of publication, the editions indicated were valid. All Recommendations and Standards are subject to revision, and parties to agreements based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent edition of the Recommendations and Standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards. The Telecommunication Standardization Bureau of ITU maintains a list of currently valid ITU-T Recommendations.

- Recommendation ITU-R BT.601-3 (1992), *Encoding parameters of digital television for studios*.
- Recommendation ITU-R BR.648 (1986), *Digital recording of audio signals*.
- Report ITU-R 955-2 (1990), *Satellite sound broadcasting with portable receivers and receivers in automobiles*.
- ISO/IEC 11172-1:1993, *Information technology – Coding of moving pictures and associated audio for digital storage media at up to about 1,5 Mbit/s – Part 1 : Systems*.
- ISO/IEC 11172-2:1993, *Information technology – Coding of moving pictures and associated audio for digital storage media at up to about 1,5 Mbit/s – Part 2 : Video*.
- ISO/IEC 11172-3:1993, *Information technology – Coding of moving pictures and associated audio for digital storage media at up to about 1,5 Mbit/s – Part 3 : Audio*.
- IEEE 1180:1990, *Standard Specifications for the Implementations of 8 by 8 Inverse Discrete Cosine Transform*.
- IEC 60908 (1999), *Audio recording – Compact disc digital audio system*.
- IEC 60461 (1986), *Time and control code for video tape recorders*.
- ITU-T Recommendation H.261 (1993), *Video codec for audiovisual services at $p \times 64$ kbit/s*.
- ITU-T Recommendation H.320 (1999), *Narrow-band visual telephone systems and terminal equipment*.
- CCITT Recommendation T.81 (1992) ISO/IEC 10918-1:1994, *Information technology – Digital compression and coding of continuous-tone still images: Requirements and guidelines. (JPEG)*.

This is a free preview. Purchase the entire publication at the link below:

- ▶ Looking for additional Standards? Visit [SAI Global Infostore](#)
- ▶ Subscribe to our [Free Newsletters about Australian Standards® in Legislation; ISO, IEC, BSI and more](#)
- ▶ Do you need to [Manage Standards Collections Online?](#)
- ▶ Learn about [LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
- ▶ Do you want to [know when a Standard has changed?](#)
- ▶ Want to [become an SAI Global Standards Sales Affiliate?](#)

Learn about other SAI Global Services:

- ▶ [LOGICOM Military Parts and Supplier Database](#)
- ▶ [Metals Infobase Database of Metal Grades, Standards and Manufacturers](#)
- ▶ [Materials Infobase Database of Materials, Standards and Suppliers](#)
- ▶ [Database of European Law, CELEX and Court Decisions](#)

Need to speak with a Customer Service Representative - [Contact Us](#)